

Specifications DMP 128 Plus

Audio system

Gain.....	Balanced output: 0 dB, unbalanced output: -6 dB
Frequency response	20 Hz to 20 kHz, ± 0.2 dB
THD + Noise	<0.01%, 20 Hz to 20 kHz, at maximum level
S/N	
Analog In to Analog Out.....	>107 dB, 20 Hz to 20 kHz, at maximum balanced output (unweighted)
Analog In to Digital Out	110 dB, 20 Hz to 20 kHz, at full-scale output (unweighted)
Digital In to Analog Out.....	115 dB, 20 Hz to 20 kHz, at maximum balanced output (unweighted)
Crosstalk	<-90 dB @ 20 Hz to 20 kHz, fully loaded
Volume control	-100 dB to 0 dB (control 0 to 100 in 0.1 dB steps)

Audio input

Number/signal type.....	12 mono, mic/line, balanced/unbalanced, 8 with phantom power, 4 without phantom power
Connectors.....	(8) 3.5 mm captive screw, 3 pole, mono, balanced/unbalanced (with phantom power) (2) 3.5 mm captive screw, 6 pole, mono, balanced/unbalanced (without phantom power)
Impedance.....	>10k ohms balanced/unbalanced
Nominal level.....	-60 dBV, +4 dBu, -10 dBV adjustable via input gain
Maximum level	+21 dBu at rated THD+N when mic gain is set to 0 dB
Equivalent input noise	<-120 dBV (1 μ Vrms) at 40 dB input gain
CMRR.....	>60 dB typical
Input gain adjustment.....	-18 dB to +80 dB in 0.1 dB steps, adjustable per input
DC phantom power	+48 VDC, $\pm 10\%$ (inputs 1-8) can be switched on or off per input

NOTE: 0 dBu = 0.775 Vrms, 0 dBV = 1 Vrms, 0 dBV \approx 2 dBu; All nominal levels are at $\pm 10\%$

Audio output

Number/signal type.....	8 mono (or 4 stereo), line, balanced/unbalanced
Connectors	(4) 3.5 mm captive screw, 6 pole, mono, balanced/unbalanced
Impedance.....	100 ohms balanced, 50 ohms unbalanced
Gain error.....	± 0.1 dB channel to channel
Maximum level (Hi-Z).....	>+21 dBu balanced, >+15 dBu unbalanced

Audio processing

A/D, D/A conversion	24-bit, 48 kHz
AEC tail length	>200 msec
AEC convergence	Up to 60 dB/sec
Noise cancellation.....	Up to 20 dB, software selectable

Specification • DMP 128 Plus (Continued)

EXP port

Transmission type	Proprietary
Connector.....	1 RJ-45
Inputs	16 channels Rx
Outputs	16 channels Tx
Audio format	Uncompressed, 24-bit, 48 kHz
EXP cable	Shielded CAT6 up to 10 meters (1 foot cable included)

USB audio port

Connector.....	1 rear panel USB mini-B
USB standards	USB 2.0, high speed

AT ports (DMP 128 Plus AT models only) — audio transport

Transmission type	Dante/AES-67, software selectable
Connectors.....	4 RJ-45, 4-port 1 Gbps switch to Dante interface
Inputs	48 channels Rx
Outputs	24 channels Tx
Audio format	Uncompressed, 24-bit, 48 kHz
Latency.....	Deterministic, based on user selections: 0.25 ms, 0.5 ms, 1.0 ms (default), 2.0 ms, 5.0 ms

VoIP Port (DMP 128 Plus V models only)

Connector.....	1 RJ-45
Data rate.....	10/100/1000 Base-T
Signaling protocol	Session Initiation Protocol (SIP), RFC 3261 and related RFCs
Discovery protocol	LLDP-MED (optional)
Lines.....	Up to 8 concurrent, independent extensions
Codec support.....	Various ITU, including wideband
Default settings	Link speed and duplex level = autodetected IP address = 192.168.1.254 Subnet mask = 255.255.255.0 Default gateway = 0.0.0.0 DHCP = off

Control/remote

Serial host control port.....	1 bidirectional RS-232, 3.5 mm captive screw, 3 pole
Baud rate and protocol.....	38400 baud, 8 data bits, 1 stop bit, no parity
Pin configuration.....	1 = Tx, 2 = Rx, 3 = G
USB control port	1 front panel USB mini-B
USB standards.....	USB 2.0, high speed
ACP control port.....	(1) 3.5 mm captive screw, 4 pole, supports up to 8 panels
Pin configuration.....	1 = +12V, 2 = +S, 3 = -S, 4 = G
Power supply	6 Watts max
Digital I/O	(8) 3.5 mm captive screw, 4 pole
Pin configuration.....	1 = In, 2 = G, 3 = Out 1, 4 = Out 2
Voltage range	Input = 0V to +12V Output = 0V (low), 5V (high) Software programmable
Ethernet host port.....	1 RJ-45
Data rate	10/100/1000 Base-T
Protocol.....	ARP, ICMP, IEEE 802.1X, IP, TCP, DHCP, HTTPS, Telnet
Default settings.....	Link speed and duplex level = autodetected IP address = 192.168.254.254 Subnet mask = 255.255.255.0 Default gateway = 0.0.0.0 DHCP = off

Specification • DMP 128 Plus (Continued)

Web server Up to 200 simultaneous sessions
Program control Extron DSP Configurator™ control/configuration program for Windows®
Extron Simple Instruction Set (SIS™)
Microsoft® Internet Explorer®, Telnet

General

Power supply Internal
Input: 100-240 VAC, 50-60 Hz

Power consumption and thermal dissipation

DMP 128 Plus

- Power consumption 29.0 W
- Thermal dissipation 66.4 BTU/hr

DMP 128 Plus C

- Power consumption 29.0 W
- Thermal dissipation 66.4 BTU/hr

DMP 128 Plus AT

- Power consumption 32.1 W
- Thermal dissipation 77.0 BTU/hr

DMP 128 Plus C V

- Power consumption 30.0 W
- Thermal dissipation 69.8 BTU/hr

DMP 128 Plus C AT

- Power consumption 32.1 W
- Thermal dissipation 77.0 BTU/hr

DMP 128 Plus C V AT

- Power consumption 32.4 W
- Thermal dissipation 78.0 BTU/hr

Temperature/humidity Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing
Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing

Cooling Fan, right to left (as viewed from the front panel), variable speed, OFF when ambient temperature is less than 40 °C

Mounting

- Rack mount Yes, with included brackets
- Furniture mount Yes, with optional under-desk mounting kit

Enclosure type Metal

Enclosure dimensions 1.69" H x 17.40" W x 9.48" D (1U high, full rack wide)
(43 mm H x 442 mm W x 241 mm D)
(Depth excludes connectors)

Product weight 4.5 lbs (2.1 kg)

Regulatory compliance CE, c-UL, UL, CE, C-Tick, FCC Class A, ICES, VCCI, RoHS, WEEE

Warranty 3 years parts and labor

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.