## **HUAWEI CloudLink Camera 200**

### 4K Ultra-HD Camera



CloudLink Camera 200

HUAWEI CloudLink Camera 200 is a next-generation 4K UHD PTZ camera that works with Huawei's UHD video conferencing endpoint range or cloud-registered soft clients, creating an unprecedented video conferencing experience.

#### · Designed with Elegance

The camera 200 was built with the integrator in mind, enabling ultra-wide field of view and powerful zoom capabilities. The professional-grade and elegant appearance adds to the aesthetics that delights the customer.

#### Effortless to Use

Easy maintenance and configuration are made possible by the embedded OSD UI, through which the Camera 200 can be operated independently. The Camera 200 operations are also supported on the remote control or touch panel of the connected Huawei endpoint.

#### · Unmatched Video Quality

The 8.51-megapixel CMOS image sensor provides HDMI video outputs of up to 4K. Image enhancement based on human visual system and 3D video denoising based on motion estimation present images in true color and with every detail, creating the ultimate video conferencing experience. The Camera 200 provides four image modes including Standard, Natural, Vivid, and Scenery for you to choose from.

#### Intelligent Image Processing

The Camera 200 provides intelligent viewing with auto-sensing capabilities including automatic white balance (AWB), automatic exposure (AE), and automatic focus (AF).

#### High-performance Pan/Tilt/Zoom (PTZ)

The high-precision pan, tilt, and zoom (PTZ) has a localization deviation of only  $\pm 0.1^{\circ}$ , which is industry-leading. The PTZ is also fast-switching with a 170-degree-wide field of view.

#### • 12 x Optical Zoom

The high-performance AF lens support stable focusing and 12 x optical zoom for best overview, which provides ideal framing to the far end.

#### · 254 Presets

PTZ positions can be predefined. (A predefined PTZ position is named preset.) The PTZ can be adjusted to a specific position to capture desired images with just one button push through presets. Presets are saved even when the Camera 200 is turned off.

#### • USB3.0 Video Output

The Camera 200 can be connected to a laptop to deliver images through the USB3.0 port.



# **HUAWEI CloudLink Camera 200**

## Specifications

Model		
Model  Model	HUAWEI Camera 200-1080P	HUAWEI Camera 200-4K
	HOAVVEI Calliela 200-1000F	NUAVVLI CAINEIA ZUU-4K
Lens	9.E1 magapiyal 1/3.E inch CMOS	
Image sensor	8.51-megapixel, 1/2.5-inch CMOS	AV 25/20, 1000 v 50/50, 1000 v 50/50, 1000 v 25/20, v v l 720 v 50/50
Video output resolution	1080p 50/60, 1080i 50/60, 1080p 25/30, and 720p 50/60	4K 25/30, 1080p 50/60, 1080i 50/60, 1080p 25/30, and 720p 50/60
Video		
Zoom	12x optical zoom	
Max. aperture	F1.8–F3.56±5%	
Focal length	3.85–43.06 mm ±5%	
Max. horizontal/ vertical field of view	80°/50°	
Pan/Tilt angle	Pan: ±110°; tilt: ±30°	
Pan/Tilt speed	Pan: 1.7°/s (tele) to 80°/s (wide); tilt: 0.7°/s to 28°/s	
Min. illumination	3 lux (50 IRE, F1.8)	
Shutter speed	1/25–1/10000 seconds	
Number of presets	254	
Image Mode		
Image mode	Standard, Natural, Vivid, and Scenery	
Auto-Sensing		
White balance	Auto, manual, or one-button-push	
Exposure	Auto, manual, aperture priority, shutter priority, or brightness priority	
Focus	Auto, manual, or one-button-push	
Prominent Features		
Digital wide dynamic range (WDR)	Supported	
Ceiling-mounted	Supported	
Remote control (infrared)	Remote control over an endpoint through the connected camera	
Software upgrade	Software upgrade through the local USB port	
Power Supply		
Input voltage	100–240 V AC, 50–60 Hz	
Output voltage	12 V DC	
Power	≤ 12 W	
Physical Specifications		
Operating temperature	0 C to 40 C	
Dimension	Camera: 6.10 in. x 9.80 in. x 5.47 in. (155 mm x 249 mm x 139 mm) Packages: 12.60 in. x 16.73 in. x 11.22 in. (320 mm x 425 mm x 285 mm)	
Weight	Net weight: 4.23 lb (1.92 kg)	
Ports		
Video output port	1 x USB3.0 1 x HDMI 1.4b	
Control port	2 x RS232 serial port	