



MXA320 TABLE ARRAY MICROPHONE

OVERVIEW

The MXA320 is the next evolution of Shure's table array microphone that provides high quality audio capture and flexible configuration for AV conferencing environments including boardrooms, huddle rooms and conferencing rooms. It features Steerable Coverage™ Technology with onboard IntelliMix® DSP, streamlined deployment with Designer System Configuration Software and intuitive remote management via ShureCloud, all housed in a familiar, compact, low-profile design.

FEATURES

- Steerable Coverage™ Technology lobe accuracy allows users to configure up to four simultaneous polar patterns
- Onboard IntelliMix® DSP includes echo-cancellation and noise reduction to eliminate annoying distractions
- Remote device management, real-time device monitoring of device status and performance, and firmware updates with ShureCloud
- With Designer System Configuration Software, coverage can easily be viewed alongside other Microflex Ecosystem products in the room
- Housed in a familiar compact low-profile design
- Stylish round form factor complements any interior design without drawing attention
- Available in white, black, or aluminum finishes
- PoE powered
- LED status bar with configurable colors and brightness



MXA320
Table Array Microphone, Black



MXA320
Table Array Microphone, Aluminum



MXA320
Table Array Microphone, White



MXA320
Table Array Microphone, Bottom View

SPECIFICATIONS All information and specifications are subject to change.

Connector Type	RJ45 (for Ethernet)
Power Requirements	PoE Class 0
Weight	0.8 lbs. (362 g)
Product Dimensions	1.4 in. x 5.3 in. x 5.3 in. (3.6 x 13.4 x 13.4 mm)
Control Software	Shure Designer
Cable Requirements	Cat 5e or higher
Operating Temperature Range	-6.7 to 40°C (20 to 104°)
Frequency Response	(-3 dB): 100Hz to 20kHz

SKUs

MXA320W	Conferencing Table Array Microphone, White
MXA320AL	Conferencing Table Array Microphone, Aluminum
MXA320B	Conferencing Table Array Microphone, Black

AVAILABLE ACCESORIES

A310AL-FM	Flush Mount, Aluminum
A310B-FM	Flush Mount, Black

FREQUENCY RESPONSE Frequency response measured from a distance of 2 feet (61 cm)

